



See nothing, hear everything

The CWM7.5 contains a 130mm(5in) bass/mid-range Kevlar[®] driver set in a die-cast chassis and a Nautilus™ tube loaded 25mm (1in) soft dome tweeter. Utilising proven technologies such as Flowport™ the speaker also features the best quality components such as having Mundorf components on the crossover. It has a critically formed baffle constructed from glass reinforced ABS and the extra-rigidity provides a much cleaner sound reproduction.

Technical Specifications

Description	2-way in-wall system
Drive units	1x ø25mm (1in) Nautilus™ tube loaded soft dome tweeter 1x ø130mm (5in) blue Kevlar [®] cone bass/midrange
Frequency Range (-6dB)	49Hz – 28kHz
Recommended Amp Power	25 – 150w
Sensitivity SPL (2.83V, 1m)	86dB
Impedance Nominal (min)	6Ω (5Ω)
Frame height	356mm (14in)
Frame width	212mm (8.5in)
Cut-out height	336mm (13.2in)
Cut-out width	192mm (7.6in)
Reservoir box height	181mm (7.1in)
Reservoir box width	385mm (15.2in)
Reservoir box depth	60mm (2.4in)
Depth behind surface	90mm (3.6in)
Protrusion	6.5mm (0.25in)
PMK	7.5W