

Azur 350A Integrated Amplifier



- Audiophile grade toroidal transformer and substantial extruded heatsink allowing 2 x 45 watts RMS into 8 ohms
- 5 inputs, 1 Tape in, 1 Record Output
- New ALPs film type 'black box' volume pot for improved low level channel balance and stereo imaging
- Speakers B connection for connection of additional pair of speakers
- New low dissipation polypropylene signal capacitors and custom made electrolytic capacitors in critical positions
- Brand new wrap-around casework design with substantially thicker brushed aluminium front panel
- Front mounted 3.5mm iPod/MP3 player connection
- Available in black or silver finishes

Detailed Specifications

Power Output	45 watts (into 8 ohms)
THD (unweighted)	<0.02% @ 1kHz, 80% of rated power <0.15% 20Hz – 20kHz, 80% of rated power
Inputs	5 inputs, 1 Tape Input, 1/4" headphone input, 3.5mm MP3 input
Outputs	Speaker A & B outputs, 1 Record Output
Frequency response (-1dB)	5Hz – 50kHz
S/N ratio (ref 1W)	>92dB (unweighted)
Input Impedances	47k ohms
Max. Power Consumption	320W
Bass/Treble controls	Shelving, ultimate boost/cut +/-10dB @ 20Hz and +/-6dB @ 20kHz
Dimensions (H x W x D)	86 x 430 x 340mm (3.4 x 16.9 x 13.4")
Weight	6.0kg (13.2lbs)



AZUR 350A