

REFLEX COLLECTION

DATA SHEET



chario

PRIMA

Low Frequency Load
Splitted Vented Subwoofer (NRS 2 π sr & Front)

Configuration
3 way Floor-Standing Direct Array with Boxer™ Engine

Drivers
1 Tweeter 2" AirRad Shallow Conex
2 Tweeter 2" WallRad Shallow Conex
2 WooferMid 4" Straight Cell Compound
2 Subwoofer 5" Heavy Weight Natural Fibers

Sensitivity
88 dBSPL/normalized to 1 m/2.83 Vrms de-correlated L/R
Pink Noise ITU-R BS 1116-1

Low Frequency Cut Off
55 Hz @ -3dB referred to C4 WETS

Crossover Frequency
1390 Hz

Rated Impedance
Modulus 4 Ω (min 3.4) Argument $\pm 36^\circ$

Suggested Amplifier
Up to 100 W/4 Ω Average Power

Weight
16.4 kg

Size
983 x 197 x 253 mm (HxWxD)

DOPPIA

Low Frequency Load
Mutual Coupled Vented Subwoofer NRS 2π sr

Configuration
4+4 way Bookshelf Direct Array with Boxer™ Engine

Drivers
2 Tweeter 2" AirRad Shallow Conex
4 Tweeter 2" WallRad Shallow Conex
2 WooferMid 4" Straight Cell Compound
2 Subwoofer 5" Heavy Weight Natural Fibers

Sensitivity
89 dB SPL/normalized to 1 m/2.83 Vrms de-correlated L/R
Pink Noise ITU-R BS 1116-1

Low Frequency Cut Off
65 Hz @ -3dB referred to C4 WETS

Crossover Frequency
1390 Hz

Rated Impedance
Modulus 4Ω (min 3.9) Argument $\pm 36^\circ$

Suggested Amplifier
Up to 100 W/4 Ω Average Power

Weight
11.7 kg

Size
182 x 663 x 253 mm (HxWxD)

SECONDA

Low Frequency Load
Vented Subwoofer NRS 2π sr

Configuration
2 way Bookshelf Direct Array with Boxer™ Engine

Drivers
1 Tweeter 2" AirRad Shallow Conex
2 Tweeter 2" WallRad Shallow Conex
1 Woofer 5" Straight Cell Compound

Sensitivity
86 dB SPL/normalized to 1 m/2.83 Vrms de-correlated L/R
Pink Noise ITU-R BS 1116-1

Low Frequency Cut Off
72 Hz @ -3dB referred to C4 WETS

Crossover Frequency
1330 Hz

Rated Impedance
Modulus 8Ω (min 6.0) Argument $\pm 36^\circ$

Suggested Amplifier
Up to 80 W/4 Ω Average Power

Weight
7.2 kg

Size
423 x 197 x 210 mm (HxWxD)

TERZA

Low Frequency Load
Vented Subwoofer NRS 2π sr

Configuration
2 way Bookshelf Direct Array with Boxer™ Engine

Drivers
1 Tweeter 2" AirRad Shallow Conex
2 Tweeter 2" WallRad Shallow Conex
1 Woofer 4" Straight Cell Compound

Sensitivity
84 dB SPL/normalized to 1 m/2.83 Vrms de-correlated L/R
Pink Noise ITU-R BS 1116-1

Low Frequency Cut Off
85 Hz @ -3dB referred to C4 WETS

Crossover Frequency
1330 Hz

Rated Impedance
Modulus 8Ω (min 5.8) Argument $\pm 36^\circ$

Suggested Amplifier
Up to 60 W/4 Ω Average Power

Weight
3.9 kg

Size
332 x 162 x 200 mm (HxWxD)

