

# Silhouette

Raccoglie il testimone della storica serie Syntar che per sedici anni ha mietuto successi in tutto il mondo. Rinnovati gli altoparlanti, rinnovati i cabinet, rinnovata l'estetica ma lasciati inalterati i principi costruttivi e di progetto che hanno fatto di questa serie il "best buy" di riferimento. Peculiarità indiscussa di questi sistemi resta la grande duttilità di utilizzo, che consente il raggiungimento di una equilibrata riproduzione in qualsiasi tipo di ambiente, anche i meno adatti sotto il profilo acustico.


The Silhouette series of loudspeakers succeeds the renowned Syntar Loudspeakers that for sixteen years were widely recognized for their excellence. With improved drivers, superior cabinetry and modernized esthetics, these speakers represent a reference "best buy". The major advantage in using the Silhouette loudspeakers is their extreme flexibility and accurate music reproduction even in acoustic environments that are not ideally suited for this purpose.

	Silhouette 100	Silhouette 200	Silhouette 300	Silhouette 100T
<b>Low Frequency load</b>	Vented NRS	Vented NRS	Vented NRS	Vented 2pi sr (proprietary)
<b>Way</b>	2	2	3	3
<b>Drivers</b>	1 tweeter 27 mm soft dome 1 woofer 130 mm polymeric compound	1 tweeter 27 mm soft dome 1 woofer 160 mm polymeric compound	1 tweeter 27 mm soft dome 1 midrange 130 mm polymeric compound 1 woofer 160 mm polymeric compound	1 tweeter 27 mm soft dome 1 midrange 130 mm polymeric compound 1 woofer 130 mm polymeric compound
<b>Sensitivity</b>	87 dB SPL / 1m / 2.83 V	88 dB SPL / 1m / 2.83 V	88 dB SPL / 1m / 2.83 V	88 dB SPL / 1m / 2.83 V
<b>Frequency @ -3dB</b>	70-20,000 Hz	60-20,000 Hz	60-20,000 Hz	60 -20,000 Hz
<b>Xover frequencies</b>	1,650 Hz	1,750 Hz	650-1,100-1,650 Hz	260-1,600 Hz
<b>Rated impedance</b>	8 ohm	8 ohm	4 ohm	4 ohm
<b>Power amplifier (avg)</b>	30-80 W / 8 ohm	30-100 W / 8 ohm	30-100 W / 4 ohm	40-100 W / 4 ohm
<b>Size (HxWxD)</b>	340 x 165 x 290 mm	370 x 180 x 300 mm	500 x 205 x 300 mm	880 x 165 x 290 mm
<b>Weight</b>	7 kg	8 kg	9,5 kg	15 kg

	Silhouette 200T	Silhouette Dialogue	Silhouette Surround	Silhouette SW1
<b>Low Frequency load</b>	Vented 2pi sr (proprietary)	Vented back firing	Sealed 2pi sr	Vented biexponential duct
<b>Way</b>	3	2	2	Discrete power circuit
<b>Drivers</b>	1 tweeter 27 mm soft dome 1 mid 160 mm poly-compound 1 woofer 160 mm poly-comp	1 tweeter 27 mm soft dome 2 shielded woofers 130 mm poly-comp	1 tweeter 27 mm soft dome 1 woofer 130 mm polymeric compound	100 W
<b>Sensitivity</b>	89 dB SPL / 1m / 2.83 V	88 dB SPL / 1m / 2.83 V	87 dB SPL / 1m / 2.83 V	40-180 Hz
<b>Frequency @ -3dB</b>	50-20,000 Hz	80-20,000 Hz	100-20,000 Hz	200 mm
<b>Xover frequencies</b>	200-1,600 Hz	1,950 Hz	1,750 Hz	490 x 380 x 490 mm
<b>Rated impedance</b>	4 ohm	8 ohm	8 ohm	18 kg
<b>Power amplifier (avg)</b>	40-120 W / 4 ohm	30-80 W / 8 ohm	30-80 W / 8 ohm	
<b>Size (HxWxD)</b>	960 x 180 x 310 mm	185 x 490 x 210 mm	340 x 165 x 115 mm	
<b>Weight</b>	19 kg	7 kg	3 kg	

**Accessori**  
Accessories


- Stand Silhouette 100 - S1  
altezza 630 mm
- Stand Silhouette 200 - S2  
altezza 630 mm
- Stand Silhouette 300 - S3  
altezza 630 mm
- Wall bracket Silhouette Surround



## Finiture in vero legno Real Wood Finishing

Colori indicativi  
Pictures for reference only

noce / walnut



noce biondo / blond walnut



ciliegio / cherry



frassino nero / black ash

