

CLASSE

CAP-2100 - INTEGRATED AMPLIFIER

The CAP-2100 combines the separate component preamp CP-500 and CA-2100 amplifier into a single elegant and powerful package. Features include balanced and single-ended inputs, dual speaker binding posts, TFT touchscreen display, IR remote and bi-directional RS-232 control.



[click image to enlarge view](#)

model	CAP-2100
frequency response	10Hz - 22kHz \pm 0.1dB
distortion (THD + noise)	0.005% (1Vrms balanced input)
preamp section	
sensitivity	1.0Vrms (balanced input, volume 86)
S/N ratio	>90dB
channel separation	>95dB
power amp section	
power/channel (continuous) (120VAC line, 1kHz signal regulated to 1% THD + noise into resistive load, all channels driven)	
load (resistive)	
8 Ω	100W
4 Ω	200W
inputs	
single-ended inputs	3pr RCA (incl. 1pr w/phono option) / 100k Ω
single-ended tape inputs	1pr RCA / 100k Ω
balanced inputs	1pr XLR / 200k Ω
outputs	
speaker	2pr
single-ended (preamp out)	1pr RCA
balanced	none
tape out	1pr RCA
power consumption	
idle power consumption	125W
rated power consumption	260W
weights & measurements	
width	17.5" (445 mm)
depth	16.5" (419 mm) (excluding connectors)
height	4.75" (121 mm)
gross weight	59 lbs (27 kg)
net weight	50 lbs (23 kg)

Classe reserve the right to adjust specifications without notice