

FURUTECH

Bulk Cables

● Power Cables




FP-3TS762 (40m/131ft/Reel)

- Conductor: 7 bundles 35 strands · 0.16mm diameter α (Alpha) μ -OFC
- Insulation: Polyethylene (Red/Natural/Yellow) 5.2mm diameter
- Inner Sheath: Flexible PVC (Black) 12.0mm diameter
- Shield: 9 x 24 strands of 0.12mm stranded-braid α (Alpha) conductor
- Sheath: Flexible PVC (Dark Blue) approx. 15.5mm diameter. (10AWG)



FP-314Ag (50m/164ft/Reel)

- 37 strands silver-plated α (Alpha) μ -OFC Conductor · 0.25mm diameter \times 1 core plus 37 strands of 0.25mm diameter α (Alpha) μ -OFC Conductor \times 2 core
- Insulation: Polyethylene (Red/Natural/Yellow) 3.4mm diameter
- Inner Sheath: Flexible PVC (Black) 9.3mm diameter
- Shield: 9 x 24 strands of 0.12mm braided α (Alpha) conductor
- Sheath: Flexible PVC (Brown) approx. 12.9mm diameter. (14AWG)



FP-3TS20 (50m/164ft/Reel)


- Conductor: 56 inner and 29 outer Strands · 0.18mm diameter α (Alpha) -OCC
- Insulation: Polyethylene (Red/Natural/Yellow) 3.53mm diameter
- Inner Sheath: Flexible PVC (Black) 9.6mm diameter
- Shield: 9 x 24 strands of 0.12mm stranded-braid α (Alpha) conductor
- Sheath: Flexible PVC (Dark Blue) approx. 14.3mm diameter. (14AWG)

● Interconnect Balanced Cable



FA-13S (50m/164ft/Reel) Solid-Core


- Conductor: 1.3mm diameter solid-core α (Alpha) μ -OFC Conductor
- Insulation: Polypropylene (Red/White) 2.4mm diameter
- Cable Lay: Two cores twisted together with cotton yarn
- Shield: 0.12mm braided α (Alpha) Conductor
- Sheath: Flexible PVC (Dark Green) approx 8.0mm diameter (16 AWG)
- Package: 50m/Reel



FA-220 (50m/164ft/Reel)


- Conductor: 80-strand α (Alpha)-OCC Conductor · 0.18mm diameter
- Insulation: Polypropylene (Red/White) 2.4mm diameter
- Cable Lay: Two cores twisted together with cotton yarn
- Shield: 0.12mm braided α (Alpha) Conductor
- Sheath: Flexible PVC (Dark Green) approx 9.0mm diameter (14 AWG)
- Package: 50m/Reel

● Interconnect Coaxial Cable




FC-61/62/63 (100m/328ft/Reel)

- Conductor: 19-strand α (Alpha) μ -OFC · 0.2mm diameter
- Insulation: High-density polyethylene plus air-foam polyethylene 3.4mm diameter
- Shield-1: PET/Al tape wrap
- Shield-2: 0.12mm braided α (Alpha) Conductor
- Sheath: Flexible PVC (Red-61/Blue-62/Green-63), approx. 6.3mm diameter (19 AWG)
- Package: 100m/Reel




J-X Ag (50m/164ft/Reel) (Silver-Plated Wire with Teflon insulation)

- Conductor: 37-strand Silver-Plated α (Alpha) μ -OFC Conductor · 0.16mm diameter
- Insulation: Teflon plus air-foamed polyethylene 5.5mm diameter
- Shield-1: PET/Al tape wrap
- Shield-2: 0.12mm braided α (Alpha) conductor
- Sheath: Flexible PVC (Light Blue) approx. 8.0mm diameter (19 AWG)
- Package: 50m/Reel



FC-11 (50m/164ft/Reel)

- Conductor: 37-strand α (Alpha)-OCC Conductor · 0.16mm diameter
- Insulation: High-density polyethylene plus air-foam polyethylene 5.5mm diameter
- Shield: 0.12mm braided α (Alpha) Conductor
- Sheath: Flexible PVC (Blue) approx 8.0mm diameter (19 AWG)
- Package: 50m/Reel



FX- α Ag (50m/164ft/Reel) (Pure Silver Wire with Teflon Insulation)


- Conductor: 7 strands α (Alpha) pure silver conductor · 0.18mm diameter
- Insulation: Teflon plus air-foam polyethylene 3mm diameter
- Shield-1: PET/Al tape wrap
- Shield-2: 0.10mm α (Alpha) μ -OFC Conductor wire braid
- Sheath: Flexible PVC (Green) approx. 8.0mm diameter (25 AWG)
- Package: 50m/Reel

● Speaker Cable




FS-303 (100m/328ft/Reel)

- Conductor: 7 bundles 28 strands · 0.1mm diameter α (Alpha) μ -OFC Conductor
- Sheath: Flexible PVC (Pearl White) 4 x 8.4mm overall size (16 AWG)
- Package: 10m/20m/30m per blister pack, 100m/Reel



J-2T (50m/164ft/Reel)

- Conductor: 6 bundles 20 strands · 0.18mm diameter α (Alpha) μ -OFC Conductor
- Insulation: Polyethylene (Red/White) 5.1mm diameter
- Sheath: Flexible PVC (Dark Green) approx. 13.5mm diameter (14 AWG)
- Package: 50m/Reel




FS-301 (100m/328ft/Reel)

- Conductor: 7 bundles 34 strands · 0.1mm diameter α (Alpha) μ -OFC Conductor
- Insulation: Polyethylene (Red/White) 3mm diameter
- Sheath: Flexible PVC (Pearl White) approx. 7.5mm diameter (14 AWG)
- Package: 100m/Reel




J-4.1T (50m/164ft/Reel) Bi-wire

- Conductor-1: 21 strands · 0.15mm plus 6 bundles 46 strands · 0.1mm diameter α (Alpha) μ -OFC Conductor
- Conductor-2: 7 bundles 5 strands · 0.3mm diameter α (Alpha) μ -OFC Conductor
- Insulation-1: Polypropylene (for high frequencies Blue/Black) 3.6mm diameter
- Insulation-2: Polypropylene (for bass frequencies Red/White) 3.6mm diameter
- Sheath: Flexible PVC (Dark Green) approx. 11.0mm diameter (13 AWG)
- Package: 50m/Reel



FS-502 (50m/164ft/Reel)

- Conductor: 7 bundles 36 strands · 0.1mm diameter α (Alpha) μ -OFC Conductor
- Insulation: Polyethylene (Red/White) 3.0mm diameter
- Cable Lay: Two cores twisted together with cotton yarn
- Shield: PET/Al tape wrap plus 7 strands · 0.2mm α (Alpha) conductor
- Sheath: Flexible PVC (Pearl Light Blue) approx 8.0mm diameter (14 AWG)
- Package: 50m/Reel



FS-15S (50m/164ft/Reel) Solid-Core

- Conductor: 1.5mm diameter solid-core α (Alpha) μ -OFC Conductor
- Insulation-1: Teflon (Clear) 2.2mm diameter
- Insulation: Polyethylene (Red/White) 2.6mm diameter
- Cable Lay: Two cores twisted together with cotton yarn
- Shield: PET/Al tape wrap plus 7 strands · 0.2mm α (Alpha) μ -OFC Conductor
- Sheath: Flexible PVC (Dark Green) approx. 8.2mm diameter (15 AWG)
- Package: 50m/Reel