

6.5" In-Wall Speaker



R-1650-W

Perfect for those who want excellent performance, reliability and durability at an affordable price, the R-1650-W brings dynamic acoustic performance to both home and commercial environments.

The R-1650-W employs a 6.5-inch polymer-cone woofer and a large motor structure for high sensitivity and strong bass output. A 1-inch polymer-dome tweeter distributes smooth, clear highs over a wide area.

The speaker's mounting system makes installation a breeze, while its paintable aluminum grille provides added rust protection in moisture-prone areas such as bathrooms and kitchens.

While the R-1650-W will fit into our latest IK-650-W installation kit, it can also be used in conjunction with the ME-650-W fire-rated enclosure.

- Good sensitivity and power handling
- Paintable to match wall
- Packaged individually

SPECIFICATIONS

frequency response	53Hz-20kHz +/- 3dB
power handling	35 watts (140 watts peak)
sensitivity	88dB @ 2.83V/1 meter
nominal impedance	8 ohms compatible
drive components	Two-way system using one 1" (2.5cm) polymer dome, tweeter and one 6.5" (16.5cm) poly woofer
dimensions	14.3" (36.3cm) H x 9.3" (23.6cm) W
cutout dimensions	13" (33cm) H x 8" (20.3cm) W
installation kit	IK-650-W (sold separately)
weight	6.5 lbs (3 kg)
accessories	ME-650-W fire rated enclosure (sold separately)
built from	2006

www.klipsch.com
1-800-KLIPSCH

All specifications are subject to change without notice. ©2007

