

## R-24F



### 90°x90° TRACTRIX HORN

Our exclusive Tractrix® Horn technology and aluminum tweeters deliver the most impressive high-end response and greater extension, enhanced imaging and powerful dynamics. This creates the cleanest, most natural sound possible.

### LINEAR TRAVEL SUSPENSION (LTS) TWEETER

A Linear Travel Suspension minimizes distortion for enhanced, detailed performance. LTS Tweeters have been a hallmark of previous Reference lines, as well as our flagship Klipsch Palladium series, making it a core component of some of the best speakers in the world.

### SPUN COPPER IMG WOOFERS

Injection Molded Graphite (IMG) woofers are exceptionally light while being extremely rigid-providing remarkable low frequency response, with minimal cone breakup and distortion. When paired with the Tractrix Horn-loaded LTS tweeter, it provides speaker efficiency highest in its class.

### FRONT-FIRING PORT

Perfectly matched to the cabinet and woofers, the front placement design creates ideal airflow with minimal distortion.

### MDF CABINET WITH BRUSHED POLYMER VENEER FINISH

Contemporary aesthetic with absolute durability that results in a seamless integration into any décor.

### DUAL 5-WAY BINDING POSTS

Sturdy, versatile and high quality terminals that provide the benefits of bi-wiring and bi-amping.

### STRONG, FLEXIBLE, REMOVABLE GRILLE

Adds a rich, refined look that is acoustically transparent.

## SPECIFICATIONS

FREQUENCY RESPONSE	45 - 24k +-3dB
SENSITIVITY	95dB @ 2.83V / 1m
POWER HANDLING	75W RMS / 300W Peak
NOMINAL IMPEDANCE	8 Ohms Compatible
HIGH FREQUENCY HORN	90° x 90° Tractrix Horn
LOW FREQUENCY DRIVER	Two 4.5" (25.4cm) IMG woofers
CROSSOVER	1600Hz
ENCLOSURE TYPE	Bass-reflex via front firing port
INPUT TYPE	Dual Binding Posts / bi-wire / bi-amp
HEIGHT	34.75" (88.27cm) with feet
WIDTH	6.5" (16.51cm)
DEPTH	10" (25.4cm) with grille
WEIGHT	25lbs (11.34kg)
FINISH	Brushed Black Polymer Veneer
BUILT FROM	2015