

ViewSonic® VE510s LCD Displays

15" E²® SERIES ENHANCED VALUE LCD DISPLAYS



The perfect union of style and performance.

The ViewSonic VE510s 15.0" LCD displays offer an excellent upgrade from CRTs without breaking the bank. Their elegant lines, thin bezel and 5.3cm panel add a **TOUCH OF STYLE TO YOUR DESKTOP** while taking up 75% less desk space than a CRT. These panels deliver 250 cd/m² of brightness (typ) and a high 450:1 contrast ratio (typ) to bring **SHARP IMAGES AND VIVID COLOURS TO THE SCREEN**. The fast 16ms response time delivers realistic video and crisp, scrolling text. The advanced OSD lock function preserves your settings and maintains an optimised image. Choose VE510s for performance, value and style.

Distinctive design, affordable value.

... Full 15" viewable screen

Displays a full, flat 15" viewable area with crisp detail and fully saturated colour.

... 1024 x 768 native resolution

Excellent image detail with sharp text and graphics.

... High brightness and contrast

250 cd/m² brightness (typ) and 450:1 contrast ratio (typ) for rich, detailed images.

... Stylish slim-bezel design

An ultra-thin bezel lets you see more without taking up valuable desktop real estate.

... OSD/Power lock secures your settings

Prevent unauthorised changes to the menu settings. The power lock prevents the monitor from being inadvertently switched off.

... OnView® controls for superior screen adjustability

Screen adjustments are precisely made via easy to use on-screen menus.

... Fast 16ms LCD response time delivers superior motion images and clarity.

... Integrated power supply for even greater desk-top space saving.

... ViewSonic Wizard included

User-friendly Wizard software automates the setup process to deliver optimised screen performance.

... Fold-up base for easy wall mounting

... PC and Mac® compatible

... TCO'99 and ENERGY® certified

ViewSonic® 

the choice of professionals

Reliable Value

ViewSonic® VE510s LCD Displays

15" E²® SERIES ENHANCED VALUE LCD DISPLAYS



1. One-touch buttons control all major functions
2. Slim bezel with a 90-degree fold-up base
3. Space-saving design is only 5.3cm thick
4. Ultra compact, attractive design



Available colour:
Silver & Black

15.0" TFT LCD DISPLAY WITH ONVIEW® CONTROLS

LCD PANEL	Type	15" colour TFT active matrix XGA LCD
	Display Area	30.4cm horizontal x 22.8cm vertical, 38.1cm diagonal
	Optimum Resolution	1024 x 768
	Contrast Ratio	450:1 (typ)
	Viewing Angles	120° horizontal, 100° vertical @ 10:1 160° horizontal, 135° vertical @ 5:1
	Response Time	16ms (typ)
	Colour Support	16.2M colours (6-bit + 2-bit FRC)
VIDEO INPUT	Light Source	Long life, 50,000 hrs. (typ)
	Brightness	250 cd/m ² (typ)
	Panel Surface	Anti-glare
COMPATIBILITY	PC	VGA up to 1024 x 768 non-interlaced
	Mac^{®1}	Power Mac™ G3/G4 up to 1024 x 768
	CONNECTOR	Analogue 15-pin mini D-sub Power 3-pin plug (CEE22)
POWER	Voltage	AC 100–240V, 50–60Hz (+/-3) (auto switch)
	Consumption	32W (typ), ≤ 1 watt in suspend mode
USER CONTROLS	Basic	Power (soft), 1, down, up, 2
	OSD	Auto Image Adjust, Brightness, Contrast, Colour Adjust [sRGB, 9300K, 6500K (default), 5400K, User Colour], Information [Mode, Model Number, Serial Number], Manual Image Adjust [H. Size, H. Position, V. Position, Fine Tune, Sharpness], Setup Menu [Language, Resolution Notice, OSD Position, OSD Timeout, OSD Background], Memory Recall
OPERATING CONDITIONS	Temperature	0–40°C
	Humidity	10–90% (non-condensing)
DIMENSIONS	Physical	343mm (W) x 169mm (D) x 326mm (H)
WEIGHT	Net	3.0kg
REGULATIONS	TCO'99, ISO13046-2 (Class II), Energy®, TÜV/GS, MPRII, UL, c-UL, FCC-B, CB, CE, IC-B, EPA, NOM, VCCI, BSMI, PSB (S-Mark), C-Tick, GOST-R (PCT-BZ02), PCBC (B-mark), EMI/B, Green Mark	
POWER MANAGEMENT	Meets TCO'99 and ENERGY® standards	
WARRANTY	Please see: www.viewsoniceurope.com/UK/Support/warranty.htm	



ViewSonic Corporation's QMS/EMS has been registered to ISO 9001 & ISO 14001 by the British Standards Institution.

ViewSonic® 
the choice of professionals

ViewSonic Europe Limited/UK
ViewSonic House
Fleming Way, Crawley
West Sussex, RH10 9GA
United Kingdom

Tel: +44 (0) 12 93 64 39 00
Fax: +44 (0) 12 93 64 39 10

ViewSonic Germany
Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany

Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France
Parc des Barbanniers
1 allée des Bas Tilliers
92230 Gennevilliers
France

Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation
381 Brea Canyon Road
Walnut
California 91789-0708
USA

Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Benelux
ViewSonic Denmark
ViewSonic Finland
ViewSonic Italy
ViewSonic MEA
ViewSonic Norway
ViewSonic Spain
ViewSonic Sweden

Tel: +32 056/85 26 27
Tel: +45 70 22 11 71
Tel: +358 (0)9 5406 4070
Tel: +34 (0) 91 63 05 339
Tel: +971 (0) 4 88 11 871
Tel: +47 (0) 22 88 17 60
Tel: +34 (0) 91 63 05 339
Tel: +46 (0) 8 50 71 30 00

¹ Adapter may be required. Specifications subject to change without notice. Selection, offers and programmes may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2005 ViewSonic Corporation. All rights reserved. VE510s 10/05-UK

For more product information, visit us on the web at www.ViewSonicEurope.com

Specifications