

# ViewSonic® VE910 LCD Monitor

19" E2® SERIES LCD DISPLAY



## Brilliant view from your desktop.

The ViewSonic VE910 19" LCD delivers Dynamic Structure technology for seamless video and smoothly scrolling text to **ENHANCE YOUR DESKTOP EXPERIENCE**. Featuring super-fast 8ms video response time, high 550:1 contrast ratio (typ.), and 1280 x 1024 native resolution, the VE910 displays your text, graphics and video in brilliant, detailed colour. The stylish, slim panel is wall mountable, allowing you to **MAKE THE MOST OF LIMITED DESKTOP REAL ESTATE**. The anti-glare screen and wide viewing angles let you **WORK COMFORTABLY FOR HOURS**. The VE910 adds performance and style to your office while keeping you within your budget.

## Affordable high-performance.

### ...ClearMotiv™ 8ms video response time

8ms video response enables digital broadcast-quality full-motion video.

### ...Stylish slim-bezel design

An ultra-thin bezel lets you see more without taking up valuable desktop real estate.

### ...Ultra-high brightness and contrast

270 cd/m<sup>2</sup> brightness (typ.) and 550:1 contrast ratio (typ.) for rich, detailed images.

### ...Full 19" viewable

### ...1280 x 1024 resolution

### ...OSD/power lock secures your settings

Prevents changes to monitor settings and maintains an optimized image.

### ...OnView® controls for superior screen adjustability

Screen adjustments are precisely made via an easy-to-use on-screen menu.

### ...sRGB colour management

For a closer match of image display to print outs.

### ...ViewSonic Wizard included

User-friendly Wizard software automates the setup process to deliver optimized screen performance.

### ...Flat-folding base for easy wall mounting (VESA® 100mm)

### ...Integrated power supply

### ...PC and Mac® compatible

### ...Kensington® security slot

### ...TCO'03 and ENERGY qualified

ViewSonic®   
the choice of professionals

# Clear Choice

# ViewSonic® VE910 LCD Monitor

## 19" E2® SERIES LCD DISPLAY



1. One-touch buttons control all major functions
2. Slim bezel with a 90-degree fold-up base
3. Space-saving design is only 6.9cm thick
4. Ultra compact, attractive design



**Available colours:**  
Silver/Black dual tone

### 19" LCD DISPLAY WITH 8MS CLEARMOTIV™ BROADCAST QUALITY

<b>LCD</b>	<b>Type</b>	19" TN-Colour TFT Active Matrix SXGA LCD
	<b>Display Area</b>	376mm horizontal x 301mm vertical; 48.3cm diagonal
	<b>Pixel Pitch</b>	0,294mm
	<b>Optimum Resolution</b>	1280 x 1024
	<b>Pixel Clock</b>	140MHz
	<b>Contrast Ratio</b>	550:1 (typ.)
	<b>Viewing Angle</b>	140° horizontal, 135° vertical @ 10:1 160° horizontal, 160° vertical @ 5:1
	<b>Response Time</b>	8ms (typ.)
	<b>Colour Support</b>	16.2M colours (6-bit + 2-bit FRC)
	<b>Brightness</b>	270cd/m <sup>2</sup> (typ.)
	<b>Panel Surface</b>	Anti-glare 3H
<b>INPUT SIGNAL</b>	<b>Video</b>	RGB analogue (75 ohms, 0.7 Vp-p)
	<b>Sync</b>	H/V separated (TTL)
	<b>Frequency</b>	Fh: 30-82kHz, Fv: 50-85Hz
<b>COMPATIBILITY</b>	<b>PC</b>	VGA up to 1280 x 1024 (@ max. 75Hz non-interlaced)
	<b>Mac<sup>1</sup></b>	Power Mac™ G3/G4/G5 1152 x 870 (@ max. 75Hz)
<b>CONNECTOR</b>	<b>Analogue</b>	15-pin mini D-Sub (attached cable)
	<b>Power</b>	3-pin AC plug, (CEE22)
<b>POWER</b>	<b>Voltage</b>	AC 100-240V, 50-60Hz (auto switch), internal power supply
	<b>Consumption</b>	35W (typ.); ≤ 1 watt in power save mode
<b>ERGONOMICS</b>	<b>Tilt</b>	Down 5°, Up 20°
<b>CONTROLS</b>	<b>Physical</b>	Power on/off, menu, down, up, select
	<b>OSD</b>	Auto image adjust, brightness, contrast, ViewMatch® colour adjust [sRGB, 9300K, 6500K (default), 5400K, user colour (R,G,B)], information [resolution, H. frequency, V. frequency, pixel clock, model number, serial number], manual image adjust [H. size, H./V. position, fine tune, sharpness, scaling], setup menu [language (English, French, German, Italian, Spanish, Finnish, Japanese, Traditional Chinese, Simplified Chinese), resolution notice, OSD position, OSD timeout, OSD background], memory recall, OSD lock, power lock
<b>OPERATING CONDITIONS</b>	<b>Temperature</b>	0°C to 40°C
	<b>Humidity</b>	10% to 90% (non-condensation)
<b>DIMENSIONS</b>	<b>(W x H x D mm)</b>	414 x 407 x 219
<b>WEIGHT</b>	<b>Net</b>	5.4kg
<b>REGULATIONS</b>		TCO'03, CE, CB, TÜV/GS, TÜV/ERGO, ISO13406-2 (pixel fault class II), UL, cUL, FCC-B, ENERGY, EPA Energy Star, NOM, GOST-R, (SASO), ICES 003, BSMI, CCC, PSB, (C-TICK), TÜV-S
<b>POWER MANAGEMENT</b>		Meets TCO'03, ENERGY and EPA Energy Star standards
<b>PACKAGE-CONTENTS</b>		LCD display, power cable, 15-pin VGA video cable, Quick Start Guide, ViewSonic Wizard CD
<b>WARRANTY</b>		Please see: <a href="http://www.viewsoniceurope.com/UK/Support/warranty.htm">www.viewsoniceurope.com/UK/Support/warranty.htm</a>



ViewSonic Corporation's QMS/EMS has been registered to ISO 9001 & ISO 14001 by the British Standards Institution.

**ViewSonic**   
the choice of professionals

**ViewSonic Europe Limited/UK**  
ViewSonic House  
Fleming Way, Crawley  
West Sussex, RH10 9GA  
United Kingdom

Tel: +44 (0) 12 93 64 39 00  
Fax: +44 (0) 12 93 64 39 10

**ViewSonic Germany**  
Hanns-Martin-Schleyer-Straße 18A  
47877 Willlich  
Germany

Tel: +49 (0) 21 54 91 88 0  
Fax: +49 (0) 21 54 91 88 10

**ViewSonic France**  
Parc des Barbannières  
1 allée des Bas Tilliers  
92230 Gennevilliers  
France

Tel: +33 (0) 1 41 47 49 00  
Fax: +33 (0) 1 41 47 49 10

**ViewSonic Corporation**  
381 Brea Canyon Road  
Walnut  
California 91789-0708  
USA

Tel: +1 909 869 7976  
Fax: +1 909 869 7958

**ViewSonic Benelux**  
**ViewSonic Denmark**  
**ViewSonic Finland**  
**ViewSonic Italy**  
**ViewSonic MEA**  
**ViewSonic Norway**  
**ViewSonic Spain**  
**ViewSonic Sweden**

Tel: +32 056/85 26 27  
Tel: +45 70 22 11 71  
Tel: +358 (0)9 5406 4070  
Tel: +34 (0) 91 63 05 339  
Tel: +971 (0) 4 88 11 871  
Tel: +47 (0) 22 88 17 60  
Tel: +34 (0) 91 63 05 339  
Tel: +46 (0) 8 50 71 30 00

<sup>1</sup>May require optional Mac adapter