

ViewSonic® VP171s/b LCD Monitors

17" ThinEdge™ LCD Monitors



Metallic-on-black

Broaden your horizon with this ultra-narrow frame.

Whether you're a graphics professional, corporate executive, or power gamer, the VP171b (black) and VP171s (metallic-on-black) LCD monitors will enhance your productivity and enjoyment. Their **THINEDGE ULTRA-SLIM BEZEL DESIGN** enables multiple-display configurations in immaculate digital high-definition clarity for powerful multi-tasking and mixed-media data analysis. XtremeView™ wide viewing angles and ClearMotiv™ 8ms broadcast-quality video response ensure intense visual performance. Class-leading features include comprehensive **HEIGHT, PIVOT, TILT AND SWIVEL** adjustments as well as multiple digital/analogue inputs.



ThinEdge design is ideal for multi-panel setups.

Equipped like no other 17" LCD monitors.

...ThinEdge ultra-slim 15mm bezel

Maximise display productivity with ThinEdge design that enhances the visual experience with clean, minimalist borders around the active image area.

...Ideal for multiple-monitor setups

Display continuous images in multiple-panel setups. ThinEdge minimises bezel gaps between panels.

...Pivot, height and wall-mount configurations

VESA® wall-mount interface and detachable base for ergonomic flexibility with pivot, height, tilt and swivel adjustments.

...OPTISYNC multiple analogue/digital inputs

Includes one DVI-D and two analogue inputs for wide compatibility with and optimisation of a variety of video sources.

...Integrated power supply with hard power switch

...TCO'03/TCO'99² and Energy Star®

...Full 17" viewable screen

...1280 x 1024 native resolution

...High brightness and contrast

300 cd/m² brightness (typ) and 500:1 contrast ratio (typ).

...ClearMotiv™ Technology

Ultra-fast 8ms video response enables digital HD broadcast-quality full motion video at 125 FPS.

...XtremeView™ performance

140° viewing angles horizontally and 130° vertically.



Black version

ThinEdge

ViewSonic®



the choice of professionals

ViewSonic® VP171s/b LCD Monitors

17" ThinEdge™ LCD Monitors

Black version



Pivot feature saves time

Spend less time scrolling on long documents. Simply rotate your screen from landscape to portrait.

Black version



Wide-travel height adjustment

With over 10 cm of travel, this LCD fits just right.



Hard power switch

Integrated power supply

Digital DVI-D connector

Dual analogue VGA connectors

LCD PANEL	Type	17" colour TFT active matrix SXGA LCD
	Display Area	33,8cm (horizontal) X 26,9cm (vertical); 43,2cm diagonal
	Optimum Resolution	1280 x 1024
	Contrast Ratio	500:1 (typ)
	Viewing Angle	140° horizontal, 130° vertical (at 10:1) 160° horizontal, 160° vertical (at 5:1)
	Response Time	8ms (typ)
	Colour Support	16.2M colours (6-bit+2-bit FRC)
	Brightness	300 cd/m ² (typ)
	Glass Surface	Anti-glare
VIDEO INPUT	Analogue	Two RGB Analogue (75 ohms, 0.7/1.0 Vp-p)
	Digital	DVI-D (TMDS, 100 ohms)
	Frequency	F _H : 30~82kHz, f _V : 50~85Hz
	Sync	H/V separated (TTL), composite sync-on-green
COMPATIBILITY	PC	Compatible from VGA up to 1280 x 1024 non-interlaced
	Mac^{®1}	Power Mac™ G3/G4 up to 1280 x 1024
CONNECTOR	Analogue	15-pin mini D-sub
	Digital	Digital DVI-D
	Power	3-pin plug
POWER	Voltage	AC 100-240V (universal), 50-60Hz
	Consumption	33W (typ); ≤ 2 watt in power save mode
CONTROLS	Basic	Power, 1, down, up, 2
	OnView[®]	Auto image adjust, contrast, brightness, input select, colour adjust (9300K, 6500K, 5400K, 5000K, user colour), information (mode, model number, serial number), manual image adjust (H. size, H. position, V. position, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background, touch tone), memory recall
OPERATING CONDITION	Temperature	0-40°C
	Humidity	10-90% (non-condensing)
DIMENSIONS	Physical	392mm x 350mm x 238mm (w/ stand)
	(W x H x D)	371mm x 309mm x 65mm (w/o stand)
WEIGHT	Net	6.5 kg (w/ stand); 4.2 kg (w/o stand)
REGULATIONS		TCO'03/TCO'99 ² , TÜV/GS, TÜV/Ergo, ISO 13406-2 (class 2), TÜV S, UL, cUL, FCC-B, CB, CE, NOM, NEMKO, SEMKO, DEMKO, FIMKO, GOST-R, Hygienic, SASO, PCBC, VCCI, BSMI, CCC, PSB, C-TICK
POWER MANAGEMENT		Meets TCO and Energy Star [®] standards
WARRANTY		Please see: www.viewsoniceurope.com/UK/Support/warranty.htm



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic



the choice of professionals

ViewSonic Europe Limited/UK
ViewSonic House
Fleming Way, Crawley
West Sussex, RH10 9GA
United Kingdom

Tel: +44 (0) 12 93 64 39 00
Fax: +44 (0) 12 93 64 39 10

ViewSonic Germany
Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany

Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France
Parc des Barbanniers
1 allée des Bas Tilliers
92230 Gennevilliers
France

Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation
381 Brea Canyon Road
Walnut
California 91789-0708
USA

Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Benelux
ViewSonic Denmark
ViewSonic Finland
ViewSonic Italy
ViewSonic MEA
ViewSonic Norway
ViewSonic Spain
ViewSonic Sweden

Tel: +32 056/85 26 27
Tel: +45 70 22 11 71
Tel: +358 (0)9 5406 4070
Tel: +34 (0) 91 63 05 339
Tel: +971 (0) 4 88 11 871
Tel: +47 (0) 22 88 17 60
Tel: +34 (0) 91 63 05 339
Tel: +46 (0) 8 50 71 30 00

¹ May require optional Mac adapter. ² Metallic-on-black version: TCO'03, Black version: TCO'99

Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2005 ViewSonic Corporation. All rights reserved. VS VP171s/b 10/05-UK