

Brilliant viewing with an ultra-slim design.

High performance, ergonomics and eye-catching looks go hand in hand with the VP930 LCD monitor. Enjoy crystal-clear digital images with an extremely high 1000:1 contrast ratio, 170° XtremeView™ wide viewing angles and fluid motion thanks to the fast response time. With its attractive THINEDGE ULTRA-SLIM BEZEL DESIGN, it's also just the ticket for finance, graphics or other corporate professionals wanting to boost their productivity through use of multiple-display configurations. The VP930 is equipped with HEIGHT, PIVOT, TILT, AND 270° SWIVEL adjustments and handles a range of digital/analogue inputs.

VP930

**ERGONOMIC 19" LCD MONITOR
WITH PERFECT SUITE**

It's not just another professional LCD. It's a ViewSonic.



VP930 – ADAPTABLE 19" LCD MONITOR WITH PERFECT SUITE

- > **Adaptable advanced ergonomics - Height adjustable, pivot, swivel and tilt**
Provides the most comfortable viewing position for the user, enabling increased productivity.
- > **Perfect Suite™ - True control software²**
Maximum display quality is easily achieved through flexible set up wizards and menus.
- > **Perfect Suite™ - Asset control and theft deterrent**
Centralised theft control, settings and the monitors status protects corporate investments by locking monitor to system with a unique pin code.
- > **OPTISYNC® multiple analogue/ digital inputs**
Includes one DVI-D and two analogue inputs providing the IT department with maximum connectivity to multiple sources.
- > **TCO'03 and ENERGY qualified**
Providing the latest certification to ensure IT departments provide the highest standards of personal wellbeing for users and ensuring corporate environmental responsibilities are met.
- > **sRGB compliant**
Achieves accurate colour match between screen and printer.
- > **Thin Edge™ - Ideal for multi monitor setups**
Display continuous images in multiple panel set-ups. Designed for minimal bezel gaps between panels.
- > **1000:1 - Extremely high contrast ratio**
Delivers bright, vivid and saturated colours for realistic and natural images.



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic 
the choice of professionals

VP930

VIEWSONIC® 19" THINEDGE™ LCD MONITOR



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Europe Limited/UK
ViewSonic House
Fleming Way, Crawley
West Sussex, RH10 9GA
United Kingdom

Tel: +44 (0) 12 93 64 39 00
Fax: +44 (0) 12 93 64 39 10

ViewSonic Germany
Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany

Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France
Parc des Barbannières
1 allée des Bas Tilliers
92230 Gennevilliers
France

Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation
381 Brea Canyon Road
Walnut
California 91789-0708
USA

Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Benelux
ViewSonic Denmark
ViewSonic Finland
ViewSonic Italy
ViewSonic MEA
ViewSonic Norway
ViewSonic Spain
ViewSonic Sweden

Tel: +32 056/85 26 27
Tel: +45 70 22 11 71
Tel: +358 (0)9 5406 4070
Tel: +34 (0) 91 63 05 339
Tel: +971 (0) 4 88 11 871
Tel: +47 (0) 22 88 17 60
Tel: +34 (0) 91 63 05 339
Tel: +46 (0) 8 50 71 30 00

LCD PANEL	Type	19" MVA colour TFT active matrix SXGA LCD
	Display Area	376mm (horizontal) x 301mm (vertical), 483mm diagonal
	Pixel Pitch	0.294mm
	Optimum Resolution	1280 x 1024
	Bandwidth	135MHz
	Contrast Ratio	1000:1 (typ.)
	Viewing Angle	170° horizontal, 170° vertical (at 10:1)
	Response Time	8ms (grey-to-grey), 20ms (off-on-off)
	Colour Support	16.7 (8bit)
	Brightness	250cd/m ² (typ.)
	Panel Surface	Anti-glare
VIDEO INPUT	Analogue	RGB analogue (0.7/1.0 Vp-p, 75 ohms)
	Digital	DVI-D (TMDS, 100 ohms)
	Frequency	F _H : 24-82kHz, f _v : 50-85Hz
	Synchronisation	H/V separated (TTL), composite, sync on green
COMPATIBILITY	PC	Compatible from VGA up to 1280 x 1024 non-interlaced (max. 75Hz)
	Mac ^{®1}	Power Mac™ up to 1280 x 1024 (max. 75Hz)
CONNECTOR	Analogue	2 x 15-pin mini D-sub (detachable cable)
	Digital	Digital DVI-D (detachable cable)
	Power	3-pin plug (CEE22)
POWER	Voltage	AC 100-240V, 50-60Hz (Auto-Switch), internal power supply
	Consumption	35 watt (max.), ≤ 1 watt in suspend mode
ERGONOMICS	Tilt	Down 5°, up 20°
	Swivel	270° (135° left/right)
	Pivot	0°-90°
	Height Adjustment	0~135mm
CONTROLS	Basic	Soft power, menu [1], down, up, select [2], main power
	OSD	Auto image adjust, contrast, brightness, input select (D-sub 1, D-sub 2, DVI), colour adjust (sRGB, 9300K, 7500K, 6500K, 5400K, 5000K, user RGB), information (resolution, H/V frequency, pixel clock, model number, serial number), manual image adjust (H/V position, H size, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background, OSD pivot), auto white balance, OSD/power lock, memory recall
OPERATING-CONDITIONS	Temperature	0°C to 40°C
	Humidity	10% to 90% (non-condensing)
DIMENSIONS	(W x H x D mm)	412 x 491 x 289 (w /stand) 412 x 336 x 61 (w /o stand)
WEIGHT	Net	6.8kg (w/ stand); 4.2 kg (w/o stand)
REGULATIONS		TCO'03, TÜV/GS, TÜV/Ergo, ISO 13406-2 (pixel failure class II), TÜV S, UL, cUL, FCC-B (ICES), CB, CE, ICES-003B, NOM, ENERGY, Energy Star, GOST-R, Hygienic, SASO, KTL/MIC, BSMI, CCC, PSB, C-TICK, WEEE.RoHS
POWER MANAGEMENT		Meets TCO'03, ENERGY and Energy Star standards
PACKAGE CONTENTS		LCD display, power cable, 15-pin VGA video cable, DVI cable, Quick Start Guide, ViewSonic Wizard CD-ROM (User Guide/drivers/PerfectSuite software), portrait/pivot CD-ROM software
WARRANTY		Please see: www.viewsoniceurope.com/UK/Support/warranty.htm

¹ May require optional Mac adapter

² Requires optional VESA DDC/CI compatible graphics card

³ Mounting options available from 3rd party suppliers