

Speed, simplicity and sound

Treat yourself to a master stroke of aesthetic design. The 19" ViewSonic VX912 impresses with its pure lines elegant simplicity – without sacrificing performance: HIGH BRIGHTNESS AND CONTRAST values deliver EXCELLENT IMAGE QUALITY and a response time of just 8ms lends films, games and DVDs excellent fluid motion. A set of stereo speakers are cleverly hidden within the casing and this model is additionally equipped with both an analogue and digital input. This high-tech monitor is just the shot for demanding home or business users.

VX912

**19" XTREME LCD MONITOR
WITH 8MS ULTRA-FAST RESPONSE TIME**

It's not just a multimedia LCD. It's a ViewSonic.



ELEGANT DESIGN WITH MULTIMEDIA FEATURES

- > **ClearMotiv™ 8ms video response time**
Ultra-fast 8ms video response delivers broadcast-quality full motion video.
- > **Dynamic Structure™ technology**
Innovative liquid crystal composition and pixel matrix accelerates video response for seamless video and intense graphics.
- > **OptiSync® digital/analogue inputs expand your connectivity**
Multi-mode input technology supports both digital (DVI) and analogue (VGA) signals for ultimate compatibility and configuration flexibility.
- > **Multimedia enhanced**
Save workspace and enjoy rich stereo sound with invisible built-in stereo speakers.
- > **Stylish slim-bezel design**
Slim-bezel design ensures that the VX912 looks good no matter if it's on or off.
- > **Ultra-high brightness and contrast**
270 cd/m² brightness and 550:1 contrast levels deliver rich, crisp, detailed images.
- > **Full 19" viewable with 1280 x 1024 resolution**
- > **PC and Mac® compatible**



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic® 
the choice of professionals

VX912

19" XTREME LCD MONITOR WITH 8MS ULTRA-FAST RESPONSE TIME



LCD	Type	19" TN colour TFT active matrix SXGA LCD
	Display Area	37.6cm horizontal x 30.1cm vertical, 48.3cm diagonal
	Pixel Pitch	0.294mm
	Optimum Resolution	1280 x 1024
	Pixel Clock	135MHz
	Contrast Ratio	550:1 (typ.)
	Viewing Angle	140° horizontal, 125° vertical (at 10:1) 160° horizontal, 145° vertical (at 5:1)
	Response Time	8ms (off-on-off) (typ.)
	Colour Support	16.2M colours (6-bit+2-bit FRC)
	Brightness	270cd/m ²
Panel Surface	Anti-glare (3H)	
VIDEO INPUT	Analogue	RGB analogue (0.7 Vp-p, 75 ohm)
	Digital	DVI-D (TMDS, 100 ohm)
	Frequency	F _H : 30 – 82kHz, F _V : 50 – 85Hz
	Synchronisation	H/V separate (TTL), composite, sync on green
COMPATIBILITY	PC	VGA up to 1280 x 1024 non-interlaced (max. 75Hz)
	Mac ^{®1}	Power Mac™ up to 1280 x 1024 non-interlaced (max. 75Hz)
CONNECTOR	Analogue	15-pin mini D-Sub (detachable cable)
	Digital	24-pin DVI-D (detachable cable)
	Audio	3.5mm stereo audio line-in
	Power	3-pin (CEE22)
AUDIO	Speakers	2 x 1 watt
POWER	Voltage	AC 100 – 240V, 50/60Hz (auto switch), internal power supply
	Consumption	35 watt (typ.), <1 watt in power save mode
ERGONOMICS	Tilt	Down 5°, Up 20°
CONTROLS	Basic	Power on/off, menu [1], up, down, select [2]
	OSD	Auto image adjust, contrast, brightness, input select (D-sub, DVI-D), colour adjust (sRGB, 9300K, 6500K, 5400K, user RGB), information (resolution, H/V frequency, pixel clock, model number, serial number, website), manual image adjust (H/V position, H size, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), OSD/power lock, memory recall
OPERATING CONDITIONS	Temperature	0°C to 40°C
	Humidity	10% to 90% (non-condensation)
DIMENSIONS	(W x H x D mm)	431 x 468 x 201 (with stand) 431 x 370 x 66 (without stand)
	WEIGHT	Net
REGULATIONS		TCO [®] 99, NEMKO/GS ² , NEMKO/ERGO ³ , CE, CB, UL, cUL, FCC-B, ENERGY, NOM, ISO13406-2 (pixel failure class II), GOST-R (+Hygienic), (SASO), PCBC, VCCI, BSMI, CCC, (PSB), (C-TICK), Argentina-S, PSE, Green Mark
POWER MANAGEMENT		Meets TCO [®] 99 and ENERGY standards
SECURITY		Kensington [®] security port
WALL MOUNT		VESA FPMPI 100mm x 100mm
PACKAGE CONTENT		LCD Monitor, power cable, 15-pin VGA video cable, audio cable, Quick Start Guide, ViewSonic Wizard CD-ROM (User Guide/drivers)
WARRANTY		Please see: www.viewsoniceurope.com/UK/Support/warranty.htm



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Europe Limited/UK
ViewSonic House
Fleming Way, Crawley
West Sussex, RH10 9GA
United Kingdom

Tel: +44 (0) 12 93 64 39 00
Fax: +44 (0) 12 93 64 39 10

ViewSonic Germany
Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany

Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France
Parc des Barbanniers
1 allée des Bas Tilliers
92230 Gennevilliers
France

Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation
381 Brea Canyon Road
Walnut
California 91789-0708
USA

Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Benelux
ViewSonic Denmark
ViewSonic Finland
ViewSonic Italy
ViewSonic MEA
ViewSonic Norway
ViewSonic Spain
ViewSonic Sweden

Tel: +32 056/85 26 27
Tel: +45 70 22 11 71
Tel: +358 (0)9 54 06 40 70
Tel: +34 (0) 91 63 05 339
Tel: +971 (0) 4 88 11 871
Tel: +47 (0) 22 88 17 60
Tel: +34 (0) 91 63 05 339
Tel: +46 (0) 8 50 71 30 00

¹ May require optional Mac adapter. ² Equivalent to TÜV/GS. ³ Equivalent to TÜV/ERGO.

Copyright © 2005, ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. VS VX912-12/05-UK