KIOKIO

Power Amplifier



The Plinius Kiokio Power Amplifier will deliver sustained unbridled performance of full orchestra pieces yet miss no subtle detail in haunting solo vocals.

As a two channel amplifier the Kiokio will drive any speaker arrangement with consummate ease and in a multi amplifier configuration it will deliver performance and power beyond your expectations.

Visually the simplified heatsink design and removal of some classic Plinius detailing results in a more austere look than its stable

mates. The clean-cut elegance and superb finish means it is completely at home in a high-end two channel environment and is suitable for standard 19U rack installations.

The Kiokio Power Amplifier has a full array of input and output fittings and is capable of delivering in excess of 300 WPC into an 8-ohm load. It will drive

the most demanding speaker arrays with total ease and confidence and is fully protected by internal safety features.

The Kiokio is a workhorse that will perform reliably under the most demanding conditions expected by professional users and installers.



KIOKIO

Power Amplifier



POWER

310 watts continuous per channel into 8 ohms. Both channels driven from 20Hz

FREQUENCY RESPONSE

20Hz to 20kHz +0.2dB -3dB at 70 kHz

DISTORTION

Typically <0.05% THD at rated power 0.1% THD and IM worst case prior to clipping

CURRENT OUTPUT

100A short duration peak per channel Fuse protected

RISE TIME

Typically 5µs

PHASE RESPONSE

+0° at 20Hz and –14° at 20kHz

HUM AND NOISE

100dB below rated output 20Hz to 20kHz A-weighted

INPUT IMPEDANCE

47k ohms

GAIN

RCA Inputs: 32dB Balanced Inputs: 38dB

PRODUCT FEATURES

1 x RCA WBT Input
1 x XLR Neutrik Input
2 x WBT Output connection
Trigger In
Ground Lift Switch
Reduced width
Available in black or silver

DIMENSIONS

Height:212mm(8.35")Width:398mm(15.6")Depth:420mm(16.5")Weight:29kg(641b)



