## fact.<sup>®</sup>8 Ultimate purity and elegance from the fact<sup>®</sup> range



The definition of fact - noun - a thing known to be true with complete certainty

fact 8 in Rich walnut

PMC's vast knowledge of acoustic engineering gained from developing the world's leading professional loudspeakers has been distilled into the **fact** range. Only this level of understanding of the creative process, room acoustics and supreme engineering make **fact** possible.

With the phenomenal benefits of PMC's **ATL**<sup>™</sup> technology the **fact'8** floor-standing model produces the commanding power and scale that is capable of filling both medium and larger rooms with awe-inspiring dynamic sound. With its compliment of twin **fact** bass drivers and ultra high resolution **fact** tweeter, they project an all encompassing, vivid sonic picture that can be experienced by all. These cutting edge precision drivers are seamlessly integrated with a highly sophisticated 24dB per octave crossover network and, in combination with the ultimately inert **ATL**<sup>™</sup> (Advanced Transmission Line) cabinet, create an entirely natural and refined balance where vocals hang in space and are truly tangible.







Luxury, hand

or ball tips

polished ingot feet

with reversible spike



"They do everything well" Highly Recommended



"A truly great design"

"Make no mistake, this speaker is the real deal!" Issue 73



"Exceptional and highly desirable in every way" April 2010



"More than mere hi-fi, fact:8 is a great loudspeaker"





8

000 PMC

ATL

CE Z

Take control HF +1, 0, -1 LF 0, -1, -2 Audiophile grade switches provide fine-tuning, ensuring the perfect sound balance in any room, and with any source

Textured fabric meets exotic


veneers. Hidden magnets

fasten the grille, further

appearance

enhancing the seamless





With absolute transparency of audio in mind the fact Ag pure silver coated binding post is the solution

fact.8 Specifications	
Freq response	28Hz – 30kHz
Sensitivity	89dB 1w 1m
Effective ATL <sup>™</sup>	
(Advanced Transmission Line Length)	3m 9.8ft
Impedance	8 Ohms
Recommended amplifier power	40 – 300W
Drive Units	LF 2 x fact 140mm/5 ½" precision drivers
	<b>HF fact</b> <sup>®</sup> 19mm high res SONOMEX <sup>™</sup> soft dome ferrofluid cooled, with 34mm surround and <b>fact</b> <sup>®</sup> dispersion grille
Crossover Freq	1.7 kHz
Crossover type	Precision 24dB filters
Input connectors	2 pairs 4mm PMC <b>Ag</b> terminals (Bi-wire or Bi-amp)
Dimensions	H 1030mm + 25mm spikes W 155mm + 80mm ingot feet D 380mm + 23mm Ag terminal
Weight	20.0 kg 44lbs



subject to change without notice





Tiger ebony

PMC

PMC Limited 43-45 Crawley Green Road Luton LU2 0AA T +44 (0)870 4441044 F +44 (0)870 4441045 email sales@promonitor.co.uk web www.pmc-speakers.com PMC USA LLC 17952 Sky Park Circle Building 45 Suite A Irvine CA 92614 T 949 861 3350 F 949 861 3352 email sales@pmc-speakers.us web www.pmc-speakers.com The Professional Monitor Company Limited Reg No: 3328009 No. 5667 ©2009

'The trade marks FACT and fact are trade marks, and in the United Kingdom, registered trade marks, of The Professional Monitor Company Limited'