


PMC









## Making the movies

PMC has earned a reputation for creating the world's finest professional loudspeakers, used at every stage of the creative process, from scoring through mixing and post-production by some of the biggest names in the movie industry.

#### Blockbuster movies created using PMC include:

Titanic, WALL-E, Inception, Tron, The Dark Knight, Gran Torino, Kung Fu Panda, Monsters vs Aliens, Independence Day, Hulk, The Fugitive, One Fine Day, The Sixth Sense, Dinosaur, Elf, The Passion of the Christ, Die Another Day, Planet of the Apes, Finding Nemo, Chicago, Lara Croft Tomb Raider: The Cradle of Life, Pirates of the Caribbean: At World's End, Spider-Man 3, Terminator 3, American Beauty and many more.



## Technically speaking

#### The drive units

The **twenty-C** utilises the same precision drive units as the **twenty-21** and **twenty-23** models. The twin 5½" bass/ mid units, developed by PMC, have lightweight and ultra stiff natural fibre cones and provide high sensitivity and a natural balance. Teamed with the SONOLEX<sup>™</sup> 27mm fabric dome tweeter, with its dispersion grille, the **twenty-C** displays a very wide soundstage, enabling you to enjoy the surround performance wherever you are in the room.





#### The cabinet

The cabinet provides a stable platform for the drive units to operate to their optimum without adding anything to the sonic signature of the speaker. Available in a choice of three veneers: Oak, Amarone, Walnut or the high gloss Diamond Black finish, the **twenty-C** matches the other speakers in the range perfectly and enhances the home environment.

The highly braced precision engineered cabinet houses PMC's proprietary Advanced Transmission Line (*ATL*) technology. This provides the characteristic transparent midrange, a supreme bass extension from a small cabinet and a fast attacking detailed bass at all levels.

# **Specifications**

twenty ·C Freq response 45Hz – 25kHz Sensitivity 90dB 1w 1m Effective ATL™ 1.8m 5.9ft Impedance 6 Ohm Drive units LF PMC twenty series, lightweight doped 5.5"/140mm cone with cast alloy chassis HF PMC/SEAS®, 27mm twenty series, SONOLEX™ Soft dome, Ferrofluid cooled Crossover freq 1.8kHz 2 pairs 4mm sockets (Bi-amp or Bi-wire) Input connectors Dimensions **H** 172mm 6.75" **W** 520mm 20.5" **D** 270mm 10.6" (+6mm grille) Weight 9.5kg 21 lbs







twenty.C in Oak



T + 44 (0) 870 444 1044 E sales@promonitor.co.uk W www.pmc-speakers.com



### **Available finishes**

