SUPRA [®]Cables MADE IN SWEDEN

HDMI/DVI Cables



HDMI Cable



HDMI-DVI Cable

HDMI Applications

HDMI stands for High Definition Multimedia Interface. SUPRA HDMI is a high performance HDMI cable specially developed for digital audio and video signals. Connectors HDMI and DVI-D.

Supra HDMI inner cores are all insulated with PE and PE foam which make the capacitance low and the propagation velocity high.

The HDMI cable is triple shielded. All signal conductors are individually shielded and covered with an additional double common shield. The screens provide efficient protection from hum and noise caused by electro-magnetical fields.

The important wires are made of silver plated OFC copper. The silver plating of the conductor will enhance the high frequency properties of the cable.

The advantage with SUPRA HDMI are:

Silver-plated cable improves High Frequency performance for widebandwidth and efficient signal transfer.

Heavy Triple screening shield signals from external influences and prevents the digital signal to radiate into nearby components.

0.8 micron thick 24k gold-plated contacts on connectors deliver long term reliability.

Standard lengths HDMI-HDMI: 1m, 2m, 4m, 8m, 12m and 15m Standard lengths HDMI-DVI: 1m, 2m, 4m, 8m and 12m

Safety approval in accordance to UL202276, CE-marked

Application examples: DVD - Video Projector DVD - Plasma/LCD TV

7

HDMI/DVI Adapters

HDMI/DVI adapters Available adapters are:

HDMI(f) <-> DVI(m) Adapter HDMI (m) <-> DVI(f) Adapter

SUPRA [®]Cables MADE IN SWEDEN



DVI-DVI Cable

DVI Applications

DVI stands for Digital Visual Interface. SUPRA DVI is a high performance DVI cable specially developed for digital video signals. Connectors DVI-D, single-link.

Supra DVI inner cores are all insulated with PE and PE foam which make the capacitance low and the propagation velocity high.

The DVI cable is triple shielded. All signal conductors are individually shielded and covered with an additional double common shield. The screens provide efficient protection from hum and noise caused by electro-magnetical fields.

The important wires are made of silver plated OFC copper. The silver plating of the conductor will enhance the high frequency properties of the cable.

The advantage with SUPRA DVI are:

Silver-plated cable improves High Frequency performace for widebandwidth and efficient signal transfer.

Heavy Triple screening shield signals from external influences and prevents the digital signal to radiate into nearby components.

0.8 micron thick 24k gold-plated contacts on connectors deliver long term reliability.

Standard lengths DVI-DVI: 1m, 2m, 4m, 8m and 12m

Safety approval in accordance to UL202276, CE-marked

Application examples:

DVD - Video Projector DVD - Plasma/LCD TV

JENVING TECHNOLOGY AB · BASTEBACKA 112-113 · S-45991, LJUNGSKILE · SWEDEN TEL +(46)-522 698990 · FAX +(46)-522 698999 · supra@jenving.se · www.jenving.se