

# BDS 700

harman/kardon®  
by HARMAN

A 5.1-channel integrated home entertainment system that does it all – anywhere

Specifications



## ■ Harman Kardon® BDS 700

With a powerful receiver integrated with a Blu-ray Disc™/DVD/CD player and FM tuner (with RDS), the Harman Kardon® BDS 700 is a beautifully compact system that transforms the home entertainment experience, reproducing movies and music from from virtually any source with all the clarity and fidelity of the original material. It even plays iPod or iPhone files via a Harman Kardon The Bridge III dock (not included). Identical, voice-matched satellite speakers surround you with rich, realistic 3D sound. A dual-driver center speaker delivers crisp, distinct movie dialogue, while a 200-watt, downward-firing powered subwoofer adds the deep, satisfying bass that's so important in today's most popular movies.

## ■ Highlights

- Complete, integrated home theater audio system  
Everything you need for great surround sound from from virtually any movie or music source
- Components engineered to work together as a system  
The performance of separate components with the ease of use of a single integrated system
- Compact, stylish design  
The BDS 700 components deliver full-size performance in space-saving form factors styled to complement any decor
- Dolby® Digital and DTS® decoding  
You'll hear every nuance of the latest movie soundtracks as they were meant to be heard
- HDMI™ output  
1080p video and high-resolution audio through a single cable for the highest-quality picture and sound
- Reads Blu-ray Disc, DVD and CD recordings  
The BDS player reads virtually any 5-inch (12cm) or 3-inch (8cm) disc, including most recordable media
- Reads most digital music and photo file formats  
The BDS player is a true multimedia device, a single system for all your entertainment sources
- Front-panel USB port  
An easy temporary connection for portable players and flash drives
- Full-color and multi-language on-screen menus and dot-matrix display
- Easy system setup and control with a TV monitor, and system status information without one
- Learning remote  
The BDS remote is easily programmed to control your TV, cable box, satellite tuner and other devices

# BDS 700

harman/kardon®  
by HARMAN

A 5.1-channel integrated home entertainment system that does it all – anywhere

## ■ Key Features

- Digital amplifier technology – Audio signals remain in the digital domain from source to output, reducing conversion artifacts for improved quality
- Identical satellites – Voice-matched two-way speakers maintain consistent sound from speaker to speaker
- Dedicated dual-driver center speaker – Dual midrange transducers deliver distinct dialogue and are voice-matched to the satellites and magnetically shielded for placement near TV
- Compact powered subwoofer – Downward firing to extend and enhance bass response through interaction with the floor, the subwoofer features auto on/off circuitry plus volume, phase and bass-boost controls
- Extensive connectivity – Three digital inputs and two line inputs make it easy to connect other audio components to your BDS system (turntables require a separate phono preamp)
- Ethernet port – Connect your BDS system to your home network and enjoy BD-Live™ content via the Internet
- Playlist function – Recalls files stored on USB devices and CD-R discs with a minimum of button pushing
- Cover-art display – Outputs cover art from audio files with ID3 tags
- Screen-saver function – Prevents burn-in on CRT and plasma displays
- Upgradable firmware – Easily install any firmware upgrades that become available via the on-screen display
- Detachable IEC power cord – Simplifies system installation
- Gold-plated binding posts
- Headphone jack
- Speaker wall-mount hardware and all cables included

## ■ Specifications

### BDS 5 Receiver

#### Audio Section

- Continuous average power (stereo): 65 watts per channel, 20Hz – 20kHz, @ <0.1% THD, both channels driven into 6 ohms
- Multichannel power: 65 watts per channel, 20Hz – 20kHz, @ <0.1% THD, all channels driven into 6 ohms
- Input sensitivity/impedance (line inputs): 250mV/46k ohms
- Signal-to-noise ratio (IHF-A): –90dB
- Frequency response @ 1W (±0.5dB): 20Hz – 20kHz
- Slew rate: 40V/μsec

#### FM Tuner Section

- Frequency range: 87.5 – 108.0MHz (US and EU)
- Usable sensitivity (IHF): >14dBf
- Signal-to-noise ratio (mono/stereo): –60dB/–55dB
- Distortion (mono/stereo): 0.3%/0.5%
- Stereo separation: –45dB @ 1kHz
- Image rejection: –70dB
- IF rejection: –80dB

#### Disc Player Section

- Supported disc formats: 5-inch (12cm) or 3-inch (8cm) BD-Video (single-layer or double-layer), DVD-Video, DVD+R/+RW,

- DVD-R/-RW, CDDA (CD digital audio), CD-R/RW, AVCHD discs
- Region code (BD/DVD): A/1 (USA); B/2 (EU)
- Audio formats: Dolby Digital, Dolby Digital Plus, Dolby TrueHD, DTS Digital, DTS-HD™ High Resolution Audio, DTS-HD Master Audio™, PCM, WMA (DRM-free version only): WMA9, CBR @192kbps, VBR @ 355kbps, MP3: 32kbps – 320kbps bitrates, including variable bitrate encoding
- Still-image format: JPEG
- Video-signal system: NTSC (USA) or PAL (EU)
- Frequency response: 20Hz – 20kHz ±0.5dB
- Signal-to-noise ratio: –90dB (A-weighted)
- Dynamic range: 90dB (16-bit)
- THD/1kHz: DVD/CD: 0.1%
- Wow and flutter: Below measurable limits

#### Video Section

- Television format: NTSC or PAL (selectable)
- HDMI version: 1.3a, with 30/36-bit Deep Color

#### General

- Power requirement: 110V – 240V AC, 50/60Hz
- Power consumption: 110W maximum; <1W standby

#### Speaker System

- Frequency response: 45Hz – 20kHz (–6dB)

#### SAT TS9 Satellites

- Midrange transducers: 75mm (3") cone, video-shielded
- High-frequency transducer: 13mm (1/2") dome, video-shielded
- Impedance: 8 ohms nominal
- Sensitivity: 86dB @ 1 watt/1 meter
- Dimensions (H x W x D): 167mm x 100mm x 92mm (6-5/8" x 3-5/16" x 3-5/8")
- Weight: 0.6kg (1.3 lb)

#### CEN TS9 Center

- Midrange transducers: Dual 75mm (3") cone, video-shielded
- High-frequency transducer: 13mm (1/2") dome, video-shielded
- Impedance: 8 ohms nominal
- Sensitivity: 86dB @ 1 watt/1 meter
- Dimensions (H x W x D): 167mm x 100mm x 92mm (6-5/8" x 3-5/16" x 3-5/8")
- Weight: 0.6kg (1.3 lb)

#### Powered Subwoofer

- Low-frequency transducer: 8" cone
- Amplifier power: 200 watts RMS
- Enclosure type: Sealed
- External trigger voltage: 3V – 30V AC/DC
- Power requirement: 120V AC, 60Hz (USA); 220V – 240V AC, 50Hz/60Hz (EU)
- Dimensions (H x W x D): 353mm x 267mm x 267mm (13-29/32" x 10-1/2" x 10-1/2")
- Weight: 9kg (19.8 lb)
- Finish: Gloss black
- Height measurement includes feet

**HARMAN** Harman Consumer, Inc.  
8500 Balboa Boulevard, Northridge, CA 91329 USA

www.harmankardon.com

© 2010 Harman International Industries, Incorporated. All rights reserved.

Harman Kardon and CMMD (patent nos. 6,327,372 and 6,404,897) are trademarks of Harman International Industries, Incorporated, registered in the United States and/or other countries.

Dolby is a registered trademark of Dolby Laboratories. DTS is a registered trademark of DTS, Inc. Blu-ray Disc and BD-Live are trademarks of the Blu-ray Disc Association. DTS-HD and DTS-HD Master Audio are trademarks of DTS, Inc. HDMI is a trademark of HDMI Licensing LLC. iPod and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. iPod/iPhone not included.

Features, specifications and appearance are subject to change without notice.