

Pro-Ject Phono Box II

MM/MC Phono Pre-amplifier



Good sound from sound technology

- Amplification and RIAA equalisation for MM and MC cartridges
- Metal case shields the electronics from vibrational and electromagnetic interference
- Phono MM/MC selection switch located at the rear of the unit
- Small size allows installation close to record player
- Optimal channel separation through dual-mono circuitry
- Special low-noise ICs used
- Gold plated RCA connection sockets
- Outboard power supply included

Technical specifications

Input impedance, MM:	47kohms/120pF
Input impedance, MC:	100ohms/120pF
Gain, MM:	40dB
Output voltage typically:	300mV/1kHz at 3mV/1kHz (MM input)
Gain, MC:	60dB
Output voltage typically:	300mV/1kHz at 0,3mV/1kHz (MC input)
Max. output:	9,5V (1kHz)
Noise floor, MM:	86dB (94dB - A weighted)
Noise floor, MC:	68dB (75dB - A weighted)
THD, MM:	< 0,01%
THD, MC:	< 0,05%
RIAA-equalisation curve accuracy:	20Hz - 20kHz / max. 0,5dB
Outboard power supply:	16V/200mA AC, suitable for your country's mains supply
Power consumption:	16V/30mA AC
Dimension W x H x D:	103 x 38 x 115mm
Weight:	570g without power supply

The manufacturer reserves the right to alter the technical specifications without notice.



Available in silver or black finish