

Pro-Ject 9

9" precision tonearm with aluminium armtube



The tonearm's design efficiently leads parasitic vibrations away from the cartridge into the mounting board, guarantees the precise tracing of the record groove by the needle and also facilitates fine adjustment of vertical and horizontal tracing due to the following constructional details:

- Uniform material: the tonearm tube and bearing housing are constructed from aluminium.
- one piece Headshell and armtube construction.
- Inverted bearing design with four ABEC7 spec ballraces (Model Perspective, RPM 6 SB and units sold individually) or stainless steel and sapphire bearings (Model RPM 4, 2.9, 6.9).
- Arm bearing housing of solid ring type. Outside ring is open to prevent bell-mode resonances.
- Design of counterweight effectively counteracts unwanted resonances.
- Counterweight shaft lowered to record level reduces cantilever forces and dynamic wow when playing warped records.
- Solid armbase permits accurate height adjustment of armtube and VTA (vertical tracing angle).
- Single-screw fixing of armtube allows rotation for easy adjustment of needle azimuth despite fixed headshell.
- Straight armtube reduces toe-in error.
- Silicone-damped armlift can be adjusted to suit arm height.
- Highly flexible top-grade copper internal wiring.

Technical specifications Pro-Ject 9

Headshell	0,5" (12,7mm) standard
Mounting distance	212mm (platter → tonearm base, Linn standard mount)
Supplied counterweight	cartridge weight 6 - 10g
Optional counterweight	cartridge weight 3,5 - 7g
Optional counterweight	cartridge weight 8 - 12g
Effective length	9" (230mm)
Effective mass	11g
Overhang	18mm
Weight	250g (without counterweight)

The manufacturer reserves the right to alter the technical specifications without notice.