

Pro-Ject RPM 10.1 Evolution

Manual turntable with
10" tonearm and
equipment base
Pro-Ject Ground it deluxe 3



Turntable

- Chassis, motor housing and granulate filled equipment base Ground it deluxe piano-lacquered dark grey
- The equipment base Ground it deluxe rests on four individually height-adjustable magnetic field feet.
- A quiet running AC motor with a two-step pulley drives the platter's outside edge via a belt.
- The medium density fibre plinth stands on three height-adjustable Sorbothane®-damped aluminium cones. Granulate filled plinth guarantees constant damping. A supplied spirit level allows easy adjustment.
- The motor is mounted in a separate metal housing to eliminate vibration transmission.
- The resonance-optimised platter is a sandwich construction utilising an acrylic platter weighing 5,4Kg and a brass record puck.
- The magnet supported (amount of support adjustable), inverted bearing uses a stainless-steel axle carrying a ceramic ball on which the ceramic bearing plate runs.
- Central metal block optimises centre of gravity and damps main bearing.
- Connection to the phono input of the amplifier can be made with connecting cables of your taste through the gold plated phono sockets and earth screw. A standard cable is provided.
- External power supply avoids potential electro-mechanical interference.

Tonearm Pro-Ject 10cc Evolution

- The headshell and armtube are fashioned from a single piece of carbon-fibre.
- Conical armtube avoids standing wave reflections.
- Inverted tonearm bearing comprises four hardened stainless tips in ABEC7 spec ballraces.
- Rings provide very solid arm bearing housings. The massive outside ring is open to avoid resonances.
- Sorbothane®-damped counterweight effectively counteracts unwanted resonances.
- The counterweights supplied are suitable for cartridges weighing between 4 - 6g, 5 - 8g, 6 - 10g or 8 - 14g
- Counterweight shaft lowered to record level reduces cantilever forces and dynamic wow when playing warped records.
- Solid armbase permits accurate height adjustment of armtube and VTA (vertical tracing angle).
- Single-screw fixing of armtube allows rotation for easy adjustment of needle azimuth despite fixed headshell.
- Silicone-damped armlift can be adjusted to suit working height of the arm.
- The internal wiring consists of flexible high-purity copper from the headshell right through to the gold-plated phono sockets.

Dimensions turntable, W x H x D: Including motor unit 480 x 210 x 330mm.

Dimensions equipment base Ground it deluxe 3: 500 x 80 x 400mm

Dust cover Cover it optional, W x H x D: 525 x 290 x 425mm.

The manufacturer reserves the right to alter the technical specifications without notice.